



## RECOMMENDED DEALER PRE-DELIVERY INSPECTION

All actions to be completed prior to customer handover
Please complete and return to Ariens Company Ltd



r loade demplote and retain to the company	
Product Type	Engine
☐ Ariens Zero-Turn product  Model/SKU  Serial Number:	Starting:  Check engine controls for correct and free operation (max/min revs, choke on/off)  Check the engine pulley bolt in the electric clutch ensuring it is torqued to 65-68NM (48-50lb/ft)
Tools and Packaging  Unpack machine from original packaging Check machine for damage or missing parts Inspect all components. (N.B. Claims for damage in transit must be submitted within 5 days)  Assembly Assemble machine as instructed in operators manual Check for loose fasteners Connect battery (red to positive . black to negative)	<ul> <li>□ Refer to the engine manufacturer instructions and check accordingly</li> <li>□ Start engine and check all electrics function correctly, including safety switches, console warning lights, and engagement of the cutter deck</li> <li>Check:</li> <li>□ Check all nuts and bolts for tightness including fitting of seat and steering control levers</li> <li>□ Check steering and brakes for correct operation</li> <li>□ Check tyre pressures (refer to Operators Manual)</li> <li>□ Check all other belts, pulleys and tension</li> <li>Belts:</li> </ul>
Battery  Check and note battery voltage Voltage: N.B. Failure to note the voltage will result in any future warranty claims being rejected  Fluid Levels  Check transmission oil level and bleed if required	<ul> <li>□ Cutter deck drive belt tension MUST be checked</li> <li>□ Engage cutter deck and ensure drive belts are running correctly and not fouling</li> <li>□ Deck:</li> <li>□ Check deck lifts correctly and freely</li> <li>□ Check cutter deck bearing housing's remains cool and that there is no undue vibration</li> <li>□ Place the tractor on a firm level surface and check cutter deck levels from front to back and side to side. (refer to Operators Manual)</li> </ul>
Throttle  Check the wiring loom, throttle and clutch cables are secure and not trapped or fouling linkages, drives or exhaust.	Note any issues

© 2016 ariens company

Part No. 366040300





## **Out of Box Failures**

If any defects / damage to this machine are found when unpacking, please contact Ariens Company Ltd immediately, providing the serial number, description of failure and all part numbers that are affected. You may also be asked to provide photographic evidence.

Tel: 01844 278 800 Fax: 01844 277 020

Web: quality.ariens-uk.com

Customer Handover		
Please note: - This form must be returned with the Warranty Registration documents.		
Service Maintenance:  Complete warranty registration as instructed by distributor  Customer has been made aware of regular routine maintenance  Customer has been handed a copy of the appropriate Operator's Manual  Customer has been advised of warranty policy and service requirements  Customer has been made aware of the importance of regular routine maintenance  Safe Operation:		
☐ Give guidance on safe starting and operation of machine and advise on appropriate PPE ☐ Area inspected to ensure machine is suitable for customer's needs and any danger spots highlighted ☐ Area and application approved as suitable ☐ Approx number of acres:		
Customer	Dealership	
Name	Name	
Address Line 1Address Line 2	Address Line 1Address Line 2	
Address Line 3	Address Line 3	
Address Line 4	Address Line 4	
Postcode	Postcode	
Customer Handover	Dealer Stamp	
PDI Completed By:  Print  Signed  Customer Handover Completed  Customer Signature  Date//		

Please return this form to Ariens Company Limited, Countax House, Great Haseley Trading Estate, Great Haseley, Oxon, OX44 7PF

© 2016 ariens company